

# SJÖCONTAINERMÅTT

Standard		Door openings (mm)		Internal dimensions (mm)			Weight (kg)			Volume (m³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. gross	Tare	Max. payload	Capacity to load line
20' std	20' x 8' x 8' 6"	2,34	2,274	5,896	2,35	2,385	27	2,15	24,85	33
40' std	40' x 8' x 8' 6"	2,339	2,274	12,035	2,35	2,393	32,5	3,7	28,8	67
40' high	40' x 8' x 9' 6"	2,34	2,577	12,035	2,35	2,697	34	3,8	30,2	76
45' high	45' x 8' x 9' 6"	2,34	2,585	13,556	2,352	2,697	32,5	4,8	27,82	86

Reefer		Door openings (mm)		Internal dimensions (mm)			Weight (kg)			Volume (m³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. payload	Capacity to load line
20' std	20' x 8' x 8' 6"	2,294	2,201	5,451	2,29	2,156	30,48	2,93	27,55	27,9
40' high	40' x 8' x 9' 6"	2,278	2,473	11,578	2,28	2,425	34	4,5	29,5	64

Flat rack		Internal dimensions (mm)					Weight (kg)			
Type	Size	Length	Width	Height	Length between headers	Length between corner posts	Width between corner posts	Gross	Tare. Payload	Max. payload
20'	20' x 8' x 8' 6"	5,935	2,398	2,327	5,935	5,693	2,106	24	2,56	21,44
40'	40' x 8' x 8' 6"	12,08	2,438	2,103	12,08	11,796	2,114	30,48	5,48	25

Open-tops		Door opening (mm)		Internal dimensions (mm)			Top opening (mm)		Weight (kg)			Volume
Type	Size	Width	Height	Length	Width	Height	Length	Width	Max. gross	Tare	Max. payload	Capacity
20 open-top	20' x 8' x 8' 6"	2,286	2,251	5,919	2,34	2,286	5,425	2,223	24	2,177	21,823	32
40 open-top	40' x 8' x 8' 6"	2,289	2,253	12,043	2,338	2,272	11,622	2,162	30,48	4,3	26,18	64